



# DECLARATION OF PERFORMANCE

in accordance with Appendix III to Regulation (EU) No. 305/2011  
No. 01 0001

Type of product  
**Normal plastering mortar GP**

Identification mark  
**KEIM Universalputz-fein**  
Batch number: see packaging of product

Intended use  
**Plaster mortar for use as exterior and interior plaster  
for walls, ceilings, pillars and divider walls**

Manufacturer  
**Keimfarben GmbH, Keimstraße 16, D-86420 Diedorf**

System for evaluation and verification of constancy of performance  
**System 4**

Declared performance

Essential characteristics	Performance	Harmonized technical specification
Fire behavior	A1	EN 998-1:2010
Water absorption	W2	EN 998-1:2010
Water vapor permeability	$\mu \leq 10$	EN 998-1:2010
Tensile adhesive strength	$\geq 0.08 \text{ N/mm}^2$ at fracture pattern A, B or C	EN 998-1:2010
Thermal conductivity (Tabular value)	$\lambda_{10, \text{dry, mat}} \leq 0.82 \text{ W/(mK)}$ for P= 50 % $\lambda_{10, \text{dry, mat}} \leq 0.89 \text{ W/(mK)}$ for P= 90 %	EN 998-1:2010
Durability	NPD	EN 998-1:2010
Hazardous substances	NPD	EN 998-1:2010

The performance of the product for which this declaration of performance was issued conforms to the declared performance. The manufacturer stated in this declaration of performance bears sole responsibility for the preparation of this declaration of performance.

Signed for the manufacturer and on behalf of the manufacturer by:

Peter Jaser, Manager of quality assurance and color metrics

Diedorf, 01.07.2013

  
p. p. Peter Jaser

Appendix  
Material safety data sheet